



- NOTES:**
1. See Detail ET 619-1 for reinforcing steel size and grade.
 2. See Details ET 619-1 and -2 for cattle guard wing details. Fabricate end units to accommodate selected cattle guard wing.
 3. Minimum soil bearing 4,000 lb/ft². Place units in fine aggregate bed 3 inch thick over hand leveled soil compacted to not less than 95% density.
 4. Chamfer exposed concrete edges 3/4" unless otherwise shown. Give all concrete surfaces a Class 1 finish.
 5. Approved alternate designs may be used.

PRECAST CATTLE GUARD					
REINFORCING STEEL AND CONCRETE					
UNIT	No. of BARS	BAR MARK	LENGTH	MASS LB	CONCRETE CUYD
6'-0" END	7	B3	85"	33.1	1.89
	10	B2	74"	41.2	
	8	B1	17"	7.6	
	6	B4	26"	8.7	
	18	B6	70"	70.1	
6'-0" INTERIOR	6	B5	36"	12.0	1.90
	8	B3	85"	37.9	
	10	B2	68"	37.9	
	12	B4	26"	17.4	
	18	B6	70"	70.1	
8'-0" INTERIOR	8	B5	36"	16.0	2.34
	8	B3	85"	37.9	
	10	B2	92"	51.2	
	12	B4	26"	17.4	
	20	B6	70"	77.9	
8'-0" END	8	B5	36"	16.0	2.32
	7	B3	85"	33.1	
	10	B2	98"	54.6	
	8	B1	17"	7.6	
	6	B4	26"	8.7	
	20	B6	70"	77.9	
	6	B5	36"	12.0	

U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL HIGHWAY ADMINISTRATION
OFFICE OF FEDERAL LANDS HIGHWAY

EFLHD DETAIL

**CATTLE GUARD
PRECAST FOUNDATION**

STANDARD APPROVED FOR USE 6/2005
REVISED: 6/2008 3/2016 9/2020

DETAIL
ET 619-3

M:\Standards_and_Details\EFLHD_Detail Drawings\FP-14\FP-14_ORD_Version\Working_Details\ET619_details\ORD\std619-3-EFL-TEMP-ord.dgn [Sheet] 16 February 2021 10:23 AM