



NOTES:

- For periods as noted in Table A, pavement may be unmarked if appropriate temporary pavement markers are provided as approved by the CO.
- Typical spacing between flexible pavement markers is 40 feet as shown. In areas of severe curvature, use a spacing of 20 feet. Areas of severe curvature are shown in the plans or provided in the Temporary Pavement Markings Schedule.
- See Subsection 718.16(b) for flexible pavement markers requirements.
- When ADT > 1000 and special hazards are present, supplement the R4-1 sign at the beginning of each no passing zone with a W14-3 sign mounted on the left side of the roadway.
- Repeat R4-1 sign at 3000-foot intervals minimum.

ADT	MAXIMUM DURATION BEFORE MARKINGS ARE REQUIRED
≤ 1000	14 Days
> 1000	3 Days

NO SCALE

U.S. DEPARTMENT OF TRANSPORTATION
 FEDERAL HIGHWAY ADMINISTRATION
 OFFICE OF FEDERAL LANDS HIGHWAY

EFLHD DETAIL

FLEXIBLE PAVEMENT MARKERS FOR TEMPORARY USE WITH UNMARKED PAVEMENTS

DETAIL APPROVED FOR USE	DETAIL
APPROVED: AUGUST 2014	E635-14
REVISED: SEPTEMBER 2020	